


K 2 | SPECIFICATIONS



COMPOSITION

- 1x bar with 2 adjustable LED spotlights, l=380mm

MATERIALS

- Extruded aluminium profile (6106T5)
- AS13 Injected aluminium Spotlight
- Cap : injected 6-6 polyamide

FINISH

- Powder-coated epoxy paint
- White (RAL9003 fine texture)

LED SPOTLIGHT POWER

- 9W (2x4,5W)

TECHNOLOGY

- LED Cree XPG2 HE

COLOUR TEMPERATURE

- 3000K
- or 4000K

LIGHT OUTPUT

- Up to 600 lumens
- PMMA 25° lens

AUTONOMY

- Li-Ion battery 14,4V 50Wh
- Autonomy > 6h

CHARGER

- 3 Li-ion cell charger
- Constant charging current 1,2A
- Constant voltage 12,6V

CONTROLLING

- Manual only : 2 step dimmer (50% and 100%)

DIMENSIONS

- l295 x L50 x H80mm

WEIGHT

- 525g

TEMPERATURE RANGE


- 0°C à +40°C

NORMS

- Class III
- IP43
- IK08
- CE

WARRANTY

- 2 years
- 6 months : Li-Ion Battery on normal use




3000K LED

- Warm white
- 3 x 3000K LEDs / spot
- 9W (2 x 4,5 W)
- Included option

4000K LED

- Neutral white
- 3 x 4000K LEDs / spot
- 9W (2 x 4,5 W)
- Included option



ACCESSORY KIT

- 1 x steel counterplate
- 2 x Velcro® straps
- 2 x metallic slings
- *Additional option*

TRANSPORT CASE

- For 8 x K2
- Waterproof casing
- Ext. dimensions : 850 X 440 X 158 mm
- *Additional option*

