


# K3 | SPECIFICATIONS



## COMPOSITION

- 1x bar with 3 adjustable LED spotlights, l=380mm

## MATERIALS

- *Profile* : Extruded aluminium (6106T5)
- *Spotlight* : AS13 Injected aluminium
- *Cap* : injected 6-6 polyamide

## FINISH

- Powder-coated epoxy paint
- Anthracite grey (2100ST) or White (RAL9003 fine texture)

## LED SPOTLIGHT POWER

- 13,5W (3x4,5W)

## TECHNOLOGY

- LED Cree XPG2 HE
- *LED High CRI >90 (additional)*

## COLOUR TEMPERATURE

- CCT Tunable White
- or RGB
- or 3000K
- or 4000K

## LIGHTING SOURCE

- Standard : up to 1000 lm
- Boost mode : up to 2000 lm
- PMMA 25° lens

## AUTONOMY

- Li-Ion battery 14,4V 50Wh
- Autonomy 6h

## CHARGER

- 4 Li-ion cell charger
- Constant charging current 1,6A
- Constant voltage 16,8V

## CONTROLLING

- Manual : 3 step dimmer (25%, 50%, 100%) + Boost
- Remote : RF (Lako remote control or RF transmitter - additional)

## DIMENSIONS

- l380 x L50 x H80mm

## WEIGHT

- 715g

## TEMPERATURE RANGE

- 0°C à +40°C

## NORMS

- Class III
- IP43
- IK08
- CE

## WARRANTY

- 2 years
- 6 months : Li-Ion Battery on normal use

# OPTIONS



## 3000K LED

- Warm white
- 3 x 3000K LEDs / spot
- 13,5W (3 x 4,5 W)
- Included option

## 4000K LED

- Neutral white
- 3 x 4000K LEDs / spot
- 13,5W (3 x 4,5 W)
- Included option



## CCT LED (TUNABLE WHITE)

- Warm white + neutral white + cool white
- 3 LEDs / spot : 3000K, 4000K, 5000K
- 13,5W (3 x 4,5 W)
- Included option

## RGB LED

- 3 LEDs / spot : Red, Green, Blue
- 13,5W (3 x 4,5 W)
- Included option




## HIGH-CRI LED

- High color rendering index
- CRI > 90
- *Additional option*

## ACCESSORY KIT

- 1 x steel counterplate
- 2 x Velcro® straps
- 2 x metallic slings
- *Additional option*



## REMOTE CONTROLLING

- Lako remote or RF transmitter - sold separately
- Included option

## TRANSPORT CASE

- For 8 x K3
- Waterproof casing
- Ext. dimensions : 850 X 440 X 158 mm
- *Additional option*

